SAYBOLT INC

TROY NY OFFICE



VESSEL: T\B B-10

LABORATORY NO.: 0200499

CUSTOMER

REF. NO(S):

LABORATORY ANALYSIS REPORT

DATE: 02/09/00

INVOICE NO: EG-15970A

ANALYSIS

DESCRIPTION

Sample designated as: #6 FUEL OIL

■ Identifying Marks: SHORE TANK 15 AFTER DISC OF THE B-10 AT SPRAGUE ALBANY, NJ

Submitted by: SAYBOLT INSPECTOR

■ Client: SPRAGUE ENERGY

SAMPLES SHALL BE RETAINED BY SAYBOLT INC. FOR FORTY FIVE (4B) DAYS UNLESS OTHERWISE REQUESTED IN WHITING.

NOTES

- This laboratory report may not be published or used except in full. It shall not be used in connection with any form of advertising unless written consent is received from an officer of Saybolt Inc.
- Results were based on analysis made at the time samples were received at the laboratory.
- Sample nomenclature is designated by the customer.

VANADIUM, PPM	NITROGEN, WT PCT	WATER & SEDIMENT (BS&W), VOL PCT	VISCOSITY, SSF SEC AT 122.0 F	VISCOSITY, KIN CST AT 122.0 F	SULFUR, X-RAY, WT PCT	POUR POINT, DEG C/DEG F	ASH, WT PCT	FLASH PT., PENSKY MARTENS, DEG F	GRAVITY, API AT 60 F	TEST
SOL/DIL	D-5762	D-1796	D-445	D-445	D-4294	D-97	D-482	D-93	D-1298	METHOD
12	0.37	0.2	1/1,4	362.7	0.413	21 / / 0 F	0.027	198	16.3	RESULT

MEMBERS ASTM-API-SAE

This report is issued solely for the use of our customers and supplies only information they specifically requested. There may be other relevant information which has not been reported. Saybolt inc. will not be responsible to third parties for the contents of this report or for any omission therefrom.